

## Product information

printed: 2012-12-05

## Glossprofi 1905

revised: July 2012

### 1 Description

**GLOSSPROFI 1905** is a mild alkaline cleaning and maintenance detergent. It does not contain acids or solvents. The mixture of special stone-reactive soaps is especially designed for the use on KORODUR™ floorings and for the use on all types of finehoned or polished Terrazzo, calcareous natural stone as well as on architectural screed surfaces, concrete and cementitious industrial floorings.

Differing from common stone soaps **GLOSSPROFI 1905** does not form a build-up of layers. No alkaline build-up does harm the surface, no dirt is preserved in layers.

### 2 Use

**GLOSSPROFI 1905** is used for FIRST CLEANING and for REGULAR MAINTENANCE with auto-scrubbing machines. The mixture of special stone-reactive soaps supports the densification of pores and leads to a water-repellent surface with reduced absorption of colouring agents. To avoid most of non-removable deep staining and to reduce corrosion by aggressive liquids the flooring can be protected by special impregnators (**THILOS dünnflüssig** or **THILOS Aqua**) to achieve a water and oil-repellent surface. To maintain the water-repelling and protective effects of **GLOSSPROFI 1905** the exclusive use of **GLOSSPROFI 1905** is necessary. After usage of conventional tensed-containing cleaning detergents the "FIRST-CLEANING" process has to be repeated to restore protection effects.

### 3 Application

#### FIRST CLEANING:

Prior to the application of **GLOSSPROFI 1905** the flooring has to be cleaned using **GRUNDREINIGER säurefrei** according to the using instructions. After cleaning dilute 1 litre of **GLOSSPROFI 1905** into 5 to 10 litre of pure water. Always try first on a small surface to find out optimum dilution ratio.

Spread the dilution equally onto the floor and use white polishing pads together with a standard singlehead cleaning machine or an auto-scrubber to cross the surface four times at low working speed. Now the dilution can be furtherly diluted with water and be vacuumed to achieve a dry floor. Favourably use an auto-scrubber for best results. According to water-hardness and machine type use a defoamer.

If too much **GLOSSPROFI 1905** was applied, the soapy film can be removed by cleaning with pure water adding some **GRUNDREINIGER säurefrei**. Slight films are removed during maintenance cleaning procedures. No polishing is required, the surface can be used immediately after treatment.

#### MAINTENANCE CLEANING:

The dilution ratio of **GLOSSPROFI 1905** is depending on the use, the grade of pollution and the porosity of the flooring. The exact dosage is a matter of individual object related experience and stronger in the beginning. After a certain time (e.g. when water is visibly repelled) the dilution ratio can be reduced. The figures below can give good indication on practically proven ratio:

Daily cleaning with auto-scrubber	: 500	-	1000 ml	on	100	litres of water
Daily manual cleaning/wet mopping	: 100	-	125 ml	on	10	litres of water

Depending on the individual dilution ratio and the cleaning equipment being used, one litre **GLOSSPROFI 1905** will be enough for approx. 800 to 1500 m<sup>2</sup>. When using auto-scrubbing machinery together with very hard water, the use of **WISCHPFLEGE SP** is recommended.

### 4 Safety

**GLOSSPROFI 1905** contains alcohol, special soaps and further non hazardous supporting chemicals.

#### Working advices:

During the use of the concentrate wear alkali-proof protective clothing, gloves and eye protection.

#### Danger advices:

- S 24/25 Avoid contact with skin and eyes.
- S 26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- S 28 After contact with skin, wash immediately with soap and plenty of water.
- S 36/37 Wear suitable protective clothing and gloves.

Limitation of liability: The liability of MKS® for defective products and any claims for damages whatsoever is limited to the purchase price of products. MKS® shall not be liable for any consequential damages. No other warranty or representation is made or implied. The managing data correspond to the today's conditions of our knowledge and experiences. They cannot be supposed and advise only without obligation and contain no guarantee or a warranty of characteristics. The use of our products is to be adapted on the local conditions. We recommend to accomplish a preliminary test on suitability. And safety requirements take you please from safety data sheets.

MKS® Funke GmbH Schleiftechnik für Profis, Im Fisserhook 28, D - 46395 Bocholt  
tel.: +49 (0)2871 / 24 75 0, fax: +49 (0)2871 / 24 75 50, www.mks-funke.de, info@mks-funke.de

## Product information

printed: 2012-12-05

## Glossprofi 1905

revised: July 2012

**Storage:**

Store on a cool and dark place, protect from heat and direct sun.

**Disposal:**

According to the local disposal regulations.

### 5 Packing

Supplied in units of 1, 5 and 200 litres one-way-containers, 1000 litres one-way-containers on request

Limitation of liability: The liability of MKS® for defective products and any claims for damages whatsoever is limited to the purchase price of products. MKS® shall not be liable for any consequential damages. No other warranty or representation is made or implied. The managing data correspond to the today's conditions of our knowledge and experiences. They cannot be supposed and advise only without obligation and contain no guarantee or a warranty of characteristics. The use of our products is to be adapted on the local conditions. We recommend to accomplish a preliminary test on suitability. And safety requirements take you please from safety data sheets.

MKS® Funke GmbH Schleiftechnik für Profis, Im Fisserhook 28, D - 46395 Bocholt

tel.: +49 (0)2871 / 24 75 0, fax: +49 (0)2871 / 24 75 50, [www.mks-funke.de](http://www.mks-funke.de), [info@mks-funke.de](mailto:info@mks-funke.de)