

JohnsonDiversey Jontec Energise

Polyurethane maintainer for varnished wooden floors

F3m

Description

It's a ready to use waterborne polyurethane maintainer for varnished wooden floors. Special formulation is able to revive dull and scratched varnished wooden floors, giving a newly finished look and continuing protection against wear. Its rich formulation renews the surface while polyurethane content provides exceptional resistance. Floors maintained with **Jontec Energise** can easily be re-coated without having to sand back to the bare wood.

Key properties

- Restores shine
- Polyurethane based
- Contains no wax
- Can be mopped on the floor (It's not possible to buff)
- Meets DIN 18032

Benefits

- Renews the appearance of floor varnish
- Provides excellent resistance to new scuffs and marks
- Wax free formulation ensures the adhesion for additional application of finish
- Quickly applied without complicated procedure
- Proven slip resistance by European norms for sports floors

Use instructions

Dosage: The product is ready to use. Apply undiluted.

Application:


The floor must be clean and free of dust, polishes, waxes and oil residues. Sparingly pour the product onto the floor and evenly spread it while still wet with a polish applicator in overlapping lanes of 1-1.5m. Apply 1 coat on low to medium traffic and 2 coats in heavy traffic areas. Allow to dry approximately at least 30 minutes before applying the second coat or opening the area to traffic.

Always test floors appearance and adhesion in an inconspicuous area before use.

Technical data

- | | |
|----------------------------|-----------------------------|
| • Appearance: | White opaque liquid |
| • Relative density [20°C]: | 1.0 |
| • pH neat: | 8.5 – 9.0 |
| • Coverage: | Approx. 25ml/m ² |

The above data is typical of normal production and should not be taken as a specification.



JohnsonDiversey Jontec Energise

Safe handling and storage information

Safe handling:

Full guidance on the handling and disposal of this product is provided in a separate Material Safety Data Sheet. Only for professional users / specialists.

Storage information:

Shelf life 2 years, from the date of production in its original, unopened container.
Store in original closed containers away from extremes of temperature.

Environmental information

The surfactants used in this product are biodegradable in compliance with the requirement of EC Directives 73/404/EEC and 73/405/EEC and their subsequent amendments.

JohnsonDiversey Headquarters

Europe, Middle East, Africa
P.O. Box 40441, 3504 AE Utrecht
Maarssebroeksedijk 2
3542 DN Utrecht, The Netherlands
Tel +31 (0)30 247 69 12
Fax +31 (0)30 247 64 93
www.johnsondiversev.com