



TENDER SPECIFICATIONS KOROCLEAN

Item x.0 Part of the standard tender volume

Grinding of a KORODUR hard aggregate floor in several grinding steps, adapted to the KORODUR hard aggregate, with MKS KC 04 and KC 06 in the KOROCLEAN procedure with careful removal of the laying on cement slurry without grinding the grain structure like terrazzo.

Euro/m²

Item x.1 Optional

Grinding of the surface of a KORODUR hard aggregate screed to remove the laying on coats originating from curing / impregnation after the installation. For complete removal of such coats it may be required to carry out not only the usual working step "middle" but also the working step "coarse".

This item is considered as request item, as in certain cases it might be applied only on partial areas.

After grinding acc. to this item has been done, the grinding acc. to item x.0 is carried out to achieve a uniform nature of the surface. After the working steps coarse or semi-coarse, the granular skeleton partially may become visible.

working step "middle, KC 03"

Euro/m²

working step "coarse, KC01"

Euro/m²

Item x.2 Optional

Modification of the surface of the KORODUR hard aggregate floor after carrying out of K04 with a mixed silicate on sodium basis with high contents of solid substance for additional compaction of the fine pore-structure by formation of stable calcium-silicate compounds.

Application including all necessary working steps - see product information

Product: MKS[®] BETODUR dreimix or KOROMINERAL.

Euro/m²

Item x.3 Optional

Application of a fluorine silane with high contents of solid substance and high penetration ability, with negligible effect to the steam diffusion, to achieve a durably improved cleaning character and a reduction of greasy, oily or watery contamination.

The product can be applied on surfaces which have been modified acc. to item x.2.

Application including all necessary working steps – see product information.

Product: MKS[®] THILOS thin liquid.

Euro/m²

Item. x.4 Part of the standard tender volume

First maintenance treatment of the previously, in the KOROCLEAN procedure, grinded hard aggregate screed, to allow easy cleaning and to support the water-repellent surface function.

Product: MKS[®] GLOSSPROFI 1905

Euro/m²

Supplier

MKS[®] Funke GmbH
Fachgroßhandel für Bodenschleiftechnik
Im Fisserhook 28
46395 Bocholt

phone: +49 / (0) 2871 / 24 75 0
telefax: +49 (0) 2871 / 24 75 50
www.mks-funke.de
info@mks-funke.de