



Tender Specification Rapid Set TRU GRAY Self-Leveling

**One-layer, self-leveling design floor TRU GRAY Self-Leveling
In composite on base concrete / screed**

Project name :
Project no :

TRU GRAY Self-Leveling **Layer thickness 4 to 35 mm**

color: gray

item	performance / product	per unit €/m ²	total €
	<p>■ Pre treatment of the base concrete / screed by shot-peening or similar, high pressure water cleaning and vacuum treatment. The sub-base must meet the requirements of DIN 18365 as well as DIN 18560 part 3, line 4.1 (compressive strength > 30 N/mm², bond strength 1,5 N/mm²). Joints in the sub-base have to be taken over in the topping layer.</p> <p>■ Application of epoxy primer KORODUR TXPK (min. 400 g/m²) including sprinkling with fire-dried quartz sand, grain size 0,4 - 0,8 mm. In given case embedding of a fabric. For further information see the data sheet Epoxy primer KORODUR TXPK.</p> <p>■ TRU GRAY _____ mm thick, in flowable consistency (admixture of water 4,1 l per 22,7 kg bag). Define the correct consistency by determination of slump. The use of our "flow kits" is recommended.</p> <p>To be applied and spread on the primer within the 15 minutes working time.</p> <p>For further information see the data sheet TRU GRAY Self-Leveling.</p> <p>Processing temperature min. + 10 °C, max. + 25 °C. Manufacturer's instructions to be observed.</p> <p>Consumption per m², per mm layer thickness in middle 1,7 kg.</p> <p>■ Individual optics can be produced on site by the admixture of decorative aggregates (e.g. glass, marble).</p> <p><input type="checkbox"/></p> <p>■ Surface treatment after 24 hours</p> <p>■ Polishing Acc. to TRU Self-Leveling polishing instructions</p> <p>■ First maintenance treatment Basically, a first maintenance treatment is required, e.g. OBTEGO R-400. (Further information see data sheet OBTEGO AG, 84051 Altheim)</p> <p><u>Hints:</u> The type of surface treatment is decisive for the optical appearance, see also „General Hints on Design Floor“. Each floor is unique. For processing hints please refer to the relevant data sheet.</p>		

LV Rapid Set TRU GRAY Self-Leveling / 111217