

Professional working with Rapid Set®

Rapid Set is a high-performance fast-setting repair mortar for floors, walls, ceilings, connection and passage elements, forms and surfaces. The outstanding features of Rapid Set allow even difficult repairs and forms. The special formulation of Rapid Set stands for universal uses, fast results and easy handling.

Rapid Set[®] offers fundamental advantages compared to epoxy mortar!



As a purely mineral product, Rapid Set impresses with maximum efficiency compared to products based on epoxy resins. Besides its technical benefits and easy processing, Rapid Set also convinces by reliable availability and an extremely favorable price-performance ratio.

Test Rapid Set and get convinced.

	(Rapid Set)	EPOXY MORTAR
PRICE/COSTS	ccc significantly lower material costs	significantly higher material costs; may even increase due to shortages of raw materials and supplies
HEALTH	ell contained substances are purely mineral	resin and hardener may cause chemical burns, allergies and respiratory diseases
PROCESSING	just mix with water and process	in general, the components must be completely mixed, re-potted and re-mixed; special instructions for processing personnel required
MATERIAL CONSUMPTION	(consistency) adaptable to requirements	in general, the complete unit must be mixed; the mixing ratio of the components must be strictly kept
WORK PROTECTION	conventional work protection, wearing protective gloves and goggles recommended	in general, extensive protective clothing, protective goggles, respiratory protection as well as sufficient ventilation are required
CLEANING OF TOOLS	(with water only	in general, with acetone (highly inflammable), high cleaning costs, enormous cleaning effort
DISPOSAL	estimate dispose residual material as ordinary construction waste	residual material must be disposed in the pollutant collection facility, material that has not set must be disposed as hazardous material
FAST	fast-setting, ready for stress already in approx. 1 hour after final set	depending on the formulation between a few minutes and several hours, up to 24 hours
FIRE CLASS	(A1 - not inflammable building materials	B1 - inflammable building materials
MULTIPURPOSE	for floor, wall, ceiling, indoors and outdoors, up to 600 mm thickness, as plaster, grouting mortar, paving joint mortar	mainly for flooring areas; depending on the application, different formulations required
ENVIRONMENT	\bigcirc pure mineral, CO ₂ reduced cement technology	see disposal

THE ONE FOR ALL



Please contact us export@korodur.de



KORODUR International GmbH Wernher-von-Braun-Str. 4 D-92224 Amberg Telefon: +49 (0) 9621 47 59-0 E-Mail: info@korodur.de



Your KORODUR[®] - Partner: