

FINALLY!

THE ONE-FOR-ALL
FOR ALL DEMANDS

Proven in America since 1960, Rapid Set® products are now available in Europe exclusively by KORODUR – a breakthrough in construction.



The unique Rapid Set® technology delivers products which have superior durability, fast setting speeds and less shrinkage. This allows for a revolutionary reduction in labour. Until now each application demanded individual and specific construction chemicals. Now this "one-for-all" covers all requirements.



Thanks to KORODUR you can experience this change on your own building site. Conventional mortar is a thing of the past. The present and the future belong to Rapid Set®, the premium product for concrete repairs. You should build on it!

MANY ADVANTAGES

FOR BREAKTHROUGH RESULTS

- **FAST-SETTING
ROCK SOLID IN 1 HOUR**
- **HIGH EARLY STRENGTH
IN 1 HOUR UP TO 20 N/MM²**
- **NO PRIMER, ONLY PRE-WET**
- **FLEXIBLE WATER DOSAGE
CONSISTENCY FROM STIFF TO FLOWABLE**
- **USES: INDOOR / OUTDOOR / FLOOR /
WALL / OVERHEAD**
- **READY FOR TOP LAYERS IN APPROX. 16 HOURS
(FOR DIFFUSION-TIGHT COVERINGS)**
- **LAYER THICKNESS
FROM '0' TO 100/150 RESP. 600 MM**

EXCLUSIVELY DISTRIBUTED
IN EUROPE BY:

KORODUR Westphal Hartbeton GmbH & Co. KG
Works Bochum-Wattenscheid
Hohensteinstraße 19
44866 Bochum, Germany
Phone: +49 (0) 23 27/9457-0
Cert.: DIN EN ISO 9001:2008

SALES:

KORODUR International GmbH
Wernher-von-Braun-Straße 4
92224 Amberg, Germany
Phone: +49 (0) 96 21/47 59-0
Telefax: +49 (0) 96 21/3 23 41
info@korodur.de

www.korodur-rapidset.com

**RAPID SET – THE
BREAKTHROUGH ONE-FOR-ALL**



THE REVOLUTION IN CONSTRUCTION

Rapid Set®

LICENSE AND PRODUCTION:



THE ONE-FOR-ALL
EXCLUSIVELY FOR PROFESSIONALS

ADVANCED HIGH PERFORMANCE & UNIQUE

THE FAST AND DURABLE SOLUTION
FOR MULTIPLE REQUIREMENTS.

EASY TO USE.
4 STEPS TO A PERFECT RESULT.



LAYER THICKNESS

READY FOR TRAFFIC
Rock solid in 1 hour
After 60 minutes > 20,0 N/mm²

INITIAL SET
In 15 minutes. Extend working time by using SET Control® or very cold water

CONSISTENCY
From stiff to flowable
Water dosage from 3,0 to 4,75 l

EXTREME BOND
On properly prepared sub-base
No primer



LAYER THICKNESS

READY FOR TRAFFIC
Rock solid in 1 hour
After 60 minutes > 17,0 N/mm²

INITIAL SET
In 15 minutes. Extend working time by using SET Control® or very cold water

CONSISTENCY
From stiff to flowable
Water dosage from 3,0 to 4,5 l

EXTREME BOND
On properly prepared sub-base
No primer



LAYER THICKNESS

READY FOR TRAFFIC
Rock solid in 1 hour
After 60 minutes > 19,0 N/mm²

INITIAL SET
In 15 minutes. Extend working time by using SET Control® or very cold water

CONSISTENCY
From stiff to flowable
Water dosage from 3,0 to 4,5 l

EXTREME BOND
On properly prepared sub-base
No primer

STEP 1: PREPARATION

- Clean surface, remove loose debris, dust, cement-slurry, acids, oils, greases.
- Pre-wet thoroughly.
- No standing water.

STEP 2: MIXING

- Pour required quantity of water into the mixing container.
- While the mixer is running add Rapid Set®.
- Mixing time generally 1–3 minutes.
- NO waiting time, do NOT re-temper.

STEP 3: APPLICATION

- Can be processed using traditional methods.
- Apply final finish quickly – smoothing, trowelling, structure.
- Do NOT install in layers.
- Horizontally, vertically and overhead.

STEP 4: CURING

- Water cure (fine mist) to ensure a strong, crack-free finish.
- Keep surfaces wet for approx. 1 hour.

CONCRETE PHARMACY®

- To extend working time use SET Control®.
- For increased fluidity and workability use FLOW Control®.
- To increase the setting time use FAST accelerator.