



# KORODUR easyFinish

per 11/2022

## Processing and smoothing aid for cementitious concrete and screed systems

### DESCRIPTION

KORODUR easyFinish is a liquid, solvent-free, ready for use synthetic resin dispersion, the ideal smoothing aid. KORODUR easyFinish was specially developed as smoothing aid for cementitious systems.

### APPLICATION

KORODUR easyFinish can be used for the production of concrete and screed surfaces, on fresh to matt damp surfaces as a smoothing aid.

Spray KORODUR easyFinish onto the trowelled surface before the first smoothing pass with helicopter and work it in. The smoothing process is facilitated and the surface additionally improved.

### PROPERTIES

- ready to use
- improves the smoothing properties of the surface
- improves the surface appearance
- solvent-free
- low emission, therefore, environmentally friendly
- indoors and outdoors

### TECHNICAL DATA

<b>Condition</b>	liquid
<b>Colour</b>	bluish
<b>Density</b>	1,0 +/- 0,02 kg/m <sup>3</sup>
<b>Material consumption</b>	approx. 150 ml/m <sup>2</sup>
<b>Temperature</b> processing and surface temperature	≥ 5 °C

### PROCESSING

Stir KORODUR easyFinish before use. Apply KORODUR easyFinish as processing aid by spraying with a suitable spraying device. The surface must not show any water film, it must be matt damp. Apply KORODUR easyFinish for the first time after the last trowelling. The second and third application is done during smoothing. Puddles should be avoided. The efficiency depends on the uniformity and closeness of the applied film.

### CLEANING

Clean working tools with clear water.

### HINTS

KORODUR easyFinish is not a curing agent and does not replace the necessary after-treatment of the smoothed KORODUR industrial floor.

With respect to the intended use and suitability of surfaces, e.g. an additional coating or care treatment, object-specific preliminary tests must be carried out.

### SUPPLY

1.000 kg disposable container  
30 kg plastic can

### STORAGE

Store cool, dry and frost-free in the original container.  
Shelf life approx. 12 months. Close once opened containers immediately.

**HINTS:** Not a hazardous substance or mixture according to Regulation (EC) No. 1272/2008. WGK 1 (self-classification); hazardous to water. Avoid skin and eye contact if possible. Wear suitable protective gloves, work clothing and safety goggles. Keep out of reach of children. Follow the instructions on the containers. The specifications provided in this data sheet for application and processing are based on tests carried out by KORODUR under ideal conditions in the laboratory and acc. to the relevant technical regulations. Therefore, the indicated data don't represent directions for application or a quality agreement in the meaning of § 434 (1) BGB, no regulation in the meaning of § 434 (2) sentence 2 BGB (German Civil Code) and no guarantee for practical application. Due to the differing conditions on site, preliminary own tests and suitability checks are required before application. Please consider the currently valid product information as well as the relevant safety data sheet acc. to Regulation (EC) No. 1907/2006 in the latest version – also published on the internet: [www.korodur.de](http://www.korodur.de).



Certified  
quality management system  
DIN EN ISO 9001:2015



**KORODUR International GmbH**  
Wernher-von-Braun-Straße 4 · 92224 Amberg  
Tel. +49 (0) 9621 4759-0 · [info@korodur.de](mailto:info@korodur.de)

[www.korodur.de](http://www.korodur.de)