



The **smart** way to repair asphalt



Why **Rapid Set®** ASPHALT REPAIR MIX?

Repair of asphalt traffic areas:
fast, load bearing, efficient and sustainable

Road damage, such as potholes or frost heave on driveways and garage entries, parking lots, footpaths, public, private or commercial traffic areas, is not only a visual irritation, it's rather a safety risk. For owners, cities and municipalities, this entails a potential liability risk.

Until now, repairs were only feasible with hot asphalt, an extremely time-consuming and expensive option, or with cold asphalt, a temporary and less durable solution.

Finally, there is a durable solution on basis of cement!

ASPHALT REPAIR MIX is a high-grade repair material for the fast, easy and durable repair of damages in asphalt.

ASPHALT REPAIR MIX is a fast-setting, polymer-modified, factory-mixed asphalt repair material based on special cement technology.

Ideal where fast strength gain, durability and low-shrinkage curing are required.

ASPHALT REPAIR MIX can be applied in layer thickness of 30 - 600 mm.



FEATURES THAT CONVINC

FAST

Areas repaired with ASPHALT REPAIR MIX can be released after only 30 minutes. Thus, reducing inevitable closures or service interruptions to a minimum.

RESISTANT

ASPHALT REPAIR MIX achieves high stability and durably resists even high loads.

DURABLE

ASPHALT REPAIR MIX is the perfect solution even in challenging conditions.

EASY TO PROCESS

ASPHALT REPAIR MIX can be processed by conventional methods. The product is mixed and finished e.g. with water.

EXCELLENT ADHESION

ASPHALT REPAIR MIX can be applied without primer.

MULTIFUNCTIONAL USE

For repair of asphalt surfaces, ASPHALT REPAIR MIX can be processed in thickness of 30 - 600 mm.



Even larger areas can be economically and permanently repaired with Rapid Set® ASPHALT REPAIR MIX



EASY PROCESSING

- 1 A severely damaged asphalt surface needs repair to prevent breaking-up during frost.
- 2 The damaged asphalt is cut out and removed.
- 3 Loose rubble and soil are removed and the deepened area pre-wet (avoiding puddling).
- 4 ASPHALT REPAIR MIX is mixed and filled into the prepared area.
- 5 The filled in ASPHALT REPAIR MIX is smoothed level with the surrounding surface.
- 6 Finish with water, foil or a finishing agent (paraffincontaining).

YOUR BENEFITS

ASPHALT REPAIR MIX quickly turns damaged, uneven asphalt surfaces back into usable traffic routes that satisfy multiple requirements and offer substantial benefits:

- Surfaces can be used and walked on again without obstacles, further damage is prevented
- Unevenness is removed
- Significantly reduced noise emission
- Rapid use
- Convenient for pedestrians, cyclists, an users of strollers, walkers or wheelchairs
- Reinstatement of road safety

OUR SERVICE

- Expert advice on site
- Instruction in product processing
- Interested in other products/services, please contact us!
- We and our partners will be happy to assist you in producing a sample surface.





License & Production:



KORODUR International GmbH

Wernher-von-Braun-Str. 4 • 92224 Amberg/Germany

Phone: +49 (0) 9621 47 59-0

Telefax: +49 (0) 9621 32 341

E-Mail: info@korodur.de • www.korodur.de

Your Rapid Set® - Partner:

HINTS: This product contains cement and has an alkaline reaction with moisture/water. Therefore, protect skin and eyes. In case of contact with eyes, consult a doctor. The specifications provided in this data sheet for application and processing are based on tests carried out by KORODUR under ideal conditions in the laboratory and acc. to the relevant technical regulations. Therefore, the indicated data do not represent directions for application or a quality agreement in the meaning of 434 (1) BGB, no regulation in the meaning of §434 (2) sentence 2 BGB (German Civil Code) and no guarantee for practical application. Due to the differing conditions on site, preliminary own tests and suitability checks are required before application.